



Retail



Hospitality



Ticketing



Kiosk



Dual



Affordable & Reliable!

3 inch POS printer

SRP-330

- 2" or 3" paper choice
- Stand-alone or wall-mount
- Dual communication interface
- Reliable printing performance




BIXOLON®

HIGHLIGHTS

2" or 3" paper choice

This two-in-one printer is equipped with a 2" partition, in which you can instantly change whether you desire 2 or 3 inch receipt. No need for utility or dip switch changes.



Stand-alone or wall-mount

We have designed the printer to mount directly to the wall effortlessly without any additional accessories. Use this hole to secure the printer directly to your wall for space-saving convenience. Internal fixture keeps paper in place during printing for smooth printing job every time.




Dual communication interface

- USB V2.0 FS + Ethernet
- USB V2.0 FS + Serial
- USB V2.0 FS + Parallel



Reliable Printing Performance

- Fast printing speed: up to 200 mm/sec
- High reliability mechanism : 1.5 million cuts auto cutter, 150 km TPH
- Outstanding printing of fonts, graphics, and barcode symbologies



SPECIFICATIONS

Printer Specifications

Print Method : Direct Thermal Line Printing

Print Speed : 200 mm/sec

Print Resolution : 180 dpi

Sensor : Paper end, Paper cover open

Media Characteristics

Media Type : Receipt

Media Width : 80 mm

Media Roll Diameter : Up to 80 mm

Supply Method : Easy Paper Loading

Physical Characteristics

Dimensions (WxLxH) : 153x195x145 mm (6.02x7.68x5.70 inch)

Weight : 280 g (0.62 lbs.)

Power : AC 100~240 V; DC 24 V, 2.5 A

Auto Cutter : Built-in

Drawer Port : 2 ports

Performance Characteristics

CPU : 32 bit CISC

Memory : 64 Mbit SDRAM, 16 Mbit FlashROM

NV Image Memory : 256 Kbytes (Mono)

Receive Buffer : 4 Kbytes

User Define Buffer : 12 Kbytes

Interface (Dual) : USB V2.0 FS+Ethernet / USB V2.0 FS+Serial /
USB V2.0 FS+Parallel

Environment Characteristics

Temperature : Operating: 0~45°C (32~113°F)

Storage: -20~60°C (-4~140°F)

Humidity : Operating: 10~80% RH

Reliability

Printer Unit : 60 million lines

TPH : 150 km, 1x108 Pulses

Auto Cutter : 1.5 million cuts

Software

Emulation : BXL / POS

Driver : Windows XP / Server 2003 / Vista / Server 2008 / 7 / 8, OPOS, JPOS,
Linux CUPS, Mac Driver

Fonts/Graphics/Symbologies

Character Size : Font A: 12x24 Font B: 9x17 Font C: 9x24
KOR, CHN: 24x24

Characters Per Line : Font A: 42 Font B, C: 56, KOR, CHN: 21

Character Sets : Alphanumeric: 95 / Expanded Graphics:128x37 page
International: 32

Graphics : Supporting user-defined fonts, graphics, formats, layouts,
and logos

Barcode Symbologies : 1D: EAN 8, EAN 13, Code 39, Code 93,
Code 128, ITF, Coda Bar, UPC A, UPC E
2D: PDF417, QR Code

Accessories

Optional : USB A-B cable, 2" partition, Splash proof cover, External
buzzer, BIXOLON melodist

BR-SRP-330-EN-MAY13

Copyright © 1995-2013 BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

BIXOLON®

www.bixolon.com



BIXOLON Co., Ltd.

7~8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de