



SEE MORE. DO MORE.

Red Resin

Thermal Transfer Ribbon

Description:

Performance red resin ribbon for printing high-density bar codes and high-resolution graphics on a wide range of synthetic materials. Produces images resistant to most harsh environments: smearing, moisture, abrasion, extreme temperature and chemicals when printed on Zebra's synthetic label and tag materials.

BS 5609 Section 2 and Section 3 compliant when paired with the following materials:

- 8000T GHS Laminate
- 8000T GHS Polyester
- 8000T GHS Vinyl

Suggested Applications:

- GHS applications, specifically those requiring BS 5609 Section 2 and Section 3 compliance
- Chemical drum labeling
- Not designed for the printing of barcodes

Stock Part Numbers:

- 74801: 4.33in x 984ft, 1in core
- 74802: 6.06in x 984ft, 1in core

Technical Specifications

Red Resin	
Color	Red (PMS 187 Red)
Ink Formulation	Resin
Base Film	Polyester
Base Film Caliper	5.7 microns
Total Caliper	7.0 microns +/- 10%

Recommended Storage Conditions: 23°F to 104°F (-5°C to 40°C) at 20% to 85% RH

Shelf Life 1 year

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.